

MAHINDRA  
**4525**  
2WD

**VERSATILE & ECONOMICAL**

**46 ENGINE HP • 36 PTO HP**

**COMPACT UTILITY TRACTOR**

Tackle landscaping, material handling, light construction and digging and trenching projects in ergonomic comfort.

- # 1 selling tractor in the world
- 5-year powertrain warranty
- Attractive Financing Options
- Heavy-duty cast-iron chassis

- Professional grade components
- Japan Quality Medal Winner
- Deming Award Winner
- Industry-leading parts support



**Mahindra**

## TRACTOR 4525

ENGINE	
Type	Four stroke, direct injection, water-cooled, diesel
Cylinders	4
Cylinder Sleeve	Wet replaceable
Engine HP (kW) @ rpm	46.0 (34.3) @ 2300
Compression Ratio	19.5:1
Displacement cubic inch (cc)	167 (2732)
Fuel Tank Capacity	14.6 gallons
ELECTRICAL	
Battery Capacity	12 volt, 88 amp hours
Alternator	12 volt, 36 amps
CLUTCH	
Type	Dual
TRANSMISSION	
Type	Sliding mesh
Number of Gears	8 forward, 2 reverse
STEERING	
Type	Hydrostatic power
Pump Output (gallons per minute)	5
BRAKES	
Type	Fully enclosed dry disc
HYDRAULIC SYSTEM	
Type	Open-center, full-live hydraulic with position and draft controls
Pump Output (gallons per minute)	8.29
3-Point Linkage	Category 1 & 2 adjustable with telescopic stabilizer
Lift Capacity (lbs.)	3527 lbs.
Rear Auxiliary Remote Valves	1 spool optional
PTO	
Type	Live
PTO RPM (engine rpm)	540 @ 2058
PTO HP (kW)	36.0 (26.9)
OPERATING WEIGHT	
Total (lbs.)	4425
DIMENSIONS With AG Tires	
Overall Length Inches (mm)	116.3 (2954)
Overall Width Inches (mm)	70.0 (1778)
Turning Radius Minimum (meters)	9.5 (2.9)
TIRES Sizes & Options	
Ag (Front / Rear)	6x16 / 13.6x28

## LOADER ML232

WITH TRACTOR MODEL 4525	
Maximum Lift Height	116"
Clearance with Attachment Dumped	94"
Reach at Maximum Height	20"
Maximum Dump Angle	27°
Maximum Rollback Angle	25°
Digging Depth Below Grade	2.3"
Lift Capacity to Full Height @ Pivot Pins (lbs.)	2700 lbs.
Breakout Force @ Pivot Pins (lbs.)	4450 lbs.
Rated Flow (Tractor System)	8 gpm
Attachment Width used for specification	60"
Attachment Rated Capacity used for specification	11.0 cu. ft.
Cycle Times @ rpm	2400 rpm
Raise Boom (seconds)	5.9
Lower Boom (seconds)	3.9
Dump Attachment (seconds)	2.4
Retract Attachment (seconds)	2.6
Loader Shipping Weight (lbs.)	1410 lbs.
STANDARD ATTACHMENTS	
Bucket (size)	60"
SKID STEER ATTACHMENTS	
Bucket	✓
Bale Spear	✓
Pallet Fork	✓

