

- [Products](#)
- [Support](#)
- [About TYM](#)
- [Contacts](#)
- [Customer Review](#)
- [Team TYM Dealers](#)



- [» Features](#)
- [» Specification](#)
- [» Attachments](#)
- [» Gallery](#)

[Tractor Quick Select](#)

Model	T353
Manufacturer	Mitsubishi
Model	S4L2
HP(kw)-Gross	35(26.1)
HP(kw)	29(21.6)
Engine speed	2700
Number of cylinders	4
Displacement-cu.in. (cc)	107.3(1758)
Transfer	Dual Dry
Motor	12V.50A
Injection System Type	Indirect Fuel Injection

TYM TRACTORS



Powertrain	T353	Hydraulic system	T353	PTO	T353
Transmission type	Sync/Shuttle	Pump type	Dual Gear Pump	PTO Type	Independent
Number of Speeds	12/F 12/R	Implement pump cap.gpm(L/Min)	6.3(23.9)	PTO Control	Electric
Rated PTO speed,mph(km/h)	13.4(21.6)	Steering pump cap. gpm (L/Min)	4.3(16.2)	PTO Mid (rpm)-Option	N/A
Clutch	Wet Disc	Max Total flow gpm (L/Min)	10.6(40.1)	PTO Rear (rpm)	540/10
	Hydrostatic	Category, 3 Point Hitch	1	PTO Shaft Diameter in. (mm)	1 3/8 (31.8)
	Dry Single Plate	Hitch lift capacity, lb. (kg)	2646 (1200)		
		Rated lift capacity at 24 inches behind link ends, lb(kg)	1764(800)		
	Lift Control type		Position		
	Joy Stick Valve		Standard		
	No. of standard remote valves-option		1		
Capacities	T353	Dimensions	T353	Standards and Weights	T353
Fuel tank, U.S. gal. (L)	9.0(34)	Overall length, in. (mm) with 3P	126(3200)	Agricultural Front	7.0-1
Hydraulic system U.S. qt. (L)	7.4(7)	Overall width, in. (mm)	53.5 (1360)	Agricultural Rear	11.2-
Water capacity (with filter) U.S. qt. (L)	6.0(5.7)	Wheelbase, in. (mm)	64.5 (1640)	Industrial Front	27x11

Capacities	T353	Dimensions	T353	Standards and Weights	T
Hydr. System, U.S. gal. (L)	8.5(32)	Height to top of ROPS, in. (mm)	94.5 (2400)	Industrial Rear	12.5x
Oil qt. (L)	8.7(8.2)	Min. Ground Clearance, in. (mm)	12.8(325)	Roll Over Protection Standard	ROPS
		Min. Turn Radius, in (mm) with Brakes	94.4 (2400)	Total Weight, lb (kg)	3065
		Min. Turn Radius, in (mm) w/o brakes	116(2950)		

Model	T353HST
Manufacturer	Mitsubishi
Model	S4L2
HP(kw)-Gross	35(26.1)
Net (kw)	26(19.4)
Engine speed	2700
No. of cylinders	4
Displacement-cu.in. (cc)	107.3(1758)
Clutch	Dual Dry
Battery	12V.50A
Injection System Type	Indirect Fuel Injection

TYM TRACTORS



Powertrain	T353HST	Hydraulic system	T353HST	PTO	T35
Transmission type	HST	Pump type	Dual Gear Pump	PTO Type	Independent
No. of Speeds	Infinite/3 Range	Implement pump cap.gpm(L/Min)	6.3(23.9)	PTO Control	Electric
Forward speed, mph(km/h)	16.1(26)	Steering pump cap. gpm (L/Min)	4.3(16.2)	PTO Mid (rpm)-Option	2000
	Wet Disc	Max Total flow gpm (L/Min)	10.6(40.1)	PTO Rear (rpm)	540
	Hydrostatic	Category, 3 Point Hitch	1	PTO Shaft Diameter in. (mm)	1 3/8 (32)
	N/A	Hitch lift capacity, lb. (kg)	2646 (1200)		
		Lift capacity at 24 inches behind link ends, lb(kg)	1764(800)		
		Lift Control type	Position		
		Joy Stick Valve	Standard		
		No. of standard remote valves-option	1		

Capacities	T353HST
Oil, U.S. gal. (L)	9.0(34)
Hydraulic system U.S. qt. (L)	7.4(7)
Hydraulic system (with filter) U.S. qt. (L)	6.0(5.7)
Hydraulic System, U.S. gal. (L)	9.25(34)
Hydraulic Tank, U.S. qt. (L)	8.7(8.2)

Dimensions

Overall length, in. (mm)	111.4(2829)
Overall width, in. (mm)	52(1320)
Wheelbase, in. (mm)	66.1(1680)
Height to top of ROPS, in. (mm)	94.4(2400)
Min. Ground Clearance, in. (mm)	13.8(350)
Min. Turn Radius, in (mm) with Brakes	94.4(2400)
Min. Turn Radius, in (mm) w/o brakes	116(2950)



Agricultural Rear	11.4'
Industrial Front	27x11'
Industrial Rear	12.5x11'
Roll Over Protection Standard	ROPS
Total Weight, lb (kg)	3065



[HOME](#) | [CONTACT](#) | [FIND A DEALER](#)

